

# (KT-1000/2000 series)

## Manual Swipe Keyboard/Wedge Reader

### General Description

KT-1000/2000 series are Manual Swipe type Keyboard/RS-232 Interface Card Reader, Which can read up to tripple track of the Mag. Card.

This model is a compact-sized type that requires no power supply.

### Key Features

- Compact size
- Keyboard/RS-232 Interface Card Reader
- No power supply



### Environmental Conditions

- Operating Temperature and Humidity : -20°C to + 70°C , 0 to 95%
- Conservation Temperature and Humidity : 0°C to + 50°C , 20 to 90% (No Condensation)

 [Zoom Picture](#)

 [View PDF for Printing](#)

### Specification

Card Standard	ISO 7811/2
Power Supply	DC5V ±8%
Ripple	Less than 50mVp-p
Power Consumption	Less than 65mA
Reading Track Width	1.5mm
Operation Locus	Indoor only
Card Reeding Speed	15-120 cm/sec
Head lifetime	Min 500,000 cycles

### Ordering Information

Model	Dimensions			Model Numbering ( KDR 6XXX )						Remark
				Single			Dual		Triple	
	W	D	H	ISO 1	ISO 2	ISO 3	ISO 1/2	ISO 2/3	ISO 2/3	
KT-1200	38	135	45.7	1210	1220	1230	1250	1260	1280	Keyboard type
KT-2200	38	135	45.7	2210	2220	2230	2250	2260	2280	RS-232C