

# AS-2350 - 2D Barcodescanner



- 2D-Barcode Support
- Slim, space saving Housing
- Scans Barcodes from Displays
- Easy Integration with USB Interface

The AS-2350 2D Presentation Barcodescanner offers a modern 2D imager in a stylish and compact design of common known omnidirectional laserscanners. This powerful imager supports standard 1D barcodes as well as 2D barcodes like QR Codes or Datamatrix codes and scans them even from electronic screens like smartphone displays. The AS-2350 can therefore be used as an all-in-one point of sale barcodescanner that can for example also scan voucher or discount barcodes from customers' smartphones.

Furthermore the AS-2350 has an adjustable scanhead as well as a large scanning angle to support smaller checkout areas. Furthermore an automatic sensor detects object in front of the AS-2350 to automatically activate the barcodescanner and to return it back to a stand by mode afterwards to lower power consumptions and to protect internal parts.

The AS-2350 imager support all kind of point of sale applications with integrated USB- and serial RS232-Interfaces and can be used out of the box thanks to its included USB connection cable.

#### Benefits:

- Megapixel image ensures better performance in decoding hard-to-read barcodes
- Read all common 1D/2D barcodes from paper labels and electronic screens
- With larger angles, adjustable omni-directional scanning head meets various needs
- Image auto-induction function effectively reduces power consumption

#### Technical Specifications:

- Dimensions (H × W × D): 157 mm × 95 mm × 93 mm
- Cable: Straight 2.0 m
- Interface: USB
- Operating Mode: Hand-held, Auto-detection
- Scan Pattern: Area image
- Image Size: 1280 × 800 pixels
- Field of View (Horizontal, Vertical): 64°, 44°
- Scanning Angle: ± 70°, ± 70°, 360° (Skew, Pitch, Roll)
- Decoding Capability: All Standard 1D and 2D Barcodes
- Operating Temperature: -20° to 55° C (-4° to 131° F)