

YOU'RE AT THE BEST TO GET THE NEW IDEAS ON POS SYSTEMS



True-flat!

Emulation Bezel
Dust/water Spilt Proof

Panel PC systems
PT & PR series systems
And TM series Monitors

TM

TFT MONITORS SERIES

Built-in USB hub to boost efficiency
in Retails and Hospitality



Wall mount

Birch TM TFT monitors with VESA75 to support wall mount applications.

Desktop

Birch TM TFT monitors support cable management

TM-2600

15" (1024x768) touch monitor
built-in USB hub, tFLAT design,
aluminum panel frame

TM-1600

9.7" (1024x768)
touch monitor built-in USB hub,
aluminum panel frame



Options



MSR card reader

triple tracks MSR card reader



VFD customer display

2 lines x 20 characters.



VESA 75mm



tFLAT design

true-flat emulation with
aluminum bezel, 5-wire
resistive touch



zFLAT design

true-flat emulation with
aluminum bezel, Projected
Capacitive touch

Specification		TM1600-10	TM2600
Display	Tft lcd size	9.7" LED	15" LED
	Maximum resolution	1024 x 768 (XGA)	
	Brightness	420 cd/m ²	250 cd/m ²
	Contrast ratio	900:1	700 : 1
	Response time	24ms	16 ms
	View angles (h/v)	160 / 174	150 / 150
	Touch panel	PCT	PCT / 5 wires resistive



I/o ports	USB	2 x USB 2.0
	MSR	Standard by USB
	VFD	COM
Power adapter	12V 3A 36W	
Operation temperature	0~40 degree c at 10%~80% humidity	
Storage temperature	-20~60 degree c at 10%~80% humidity	
Compliance	FCC, CE, ROHS certificate LVD	
Dimension	9.7" / 271 (W) X 194 (L) X 251 (H) mm	
	15" / 358 (W) X 194 (L) X 330 (H) mm	