



MY PRINTER X

High-tech portable mini printer

MY PRINTER X is a high-tech portable mini printer. It is ultra-light and compact, with large paper roll (30mm diameter). High printing capacity thanks to its powerful batteries: approximately 30mt of printed paper! USB Interface. It comes with paper end sensor, supports an upgradable customer logo and prints the most used barcodes. Drivers: Windows, Linux, Android™ and iOS. Thanks to the Bluetooth® technology, MY PRINTER X can print from Android™, iOS. Practical belt hook, battery charger and USB cable included in the package.















CHARACTERISTICS

- Portable mini printer with Hi-tech design
- Ultra-light and compact: only 205g!
- Bluetooth® wireless technology and USB
- High performance: 10m printed paper
- International fonts on-board: any language available
- 1D and 2D (PDF417, QRCODE) barcodes printing
- RGB LED
- Paper thickness: 61⊠m
- Dimensions: 110mm (L) x85mm (D) x45mm (H)

BATTERIES

- Battery: Li-Ion 7.4V 1500mAh, rechargeable • Battery charger: 2A through USB cable
- Recharge cycle: 4.5 hours max.
- Performance and capacity: 30m paper; 100 hours in stand-by with Bluetooth® interface

ACCESSORIES

Protective case











TECHNICAL SHEET

Printing Method	Thermal printing
Number of dots	8 dots / mm
Resolution	203 DPI
Printing (mm/sec)	max 60 (this depends on the battery status, type of printing and environment temperature)
Character set	PC437, PC850, PC860, PC863, PC865, PC858 (Euro)
Printing Format	1x to 8x height and width, reverse, underlined, script, bold
Printing Direction	Straight, 90°, 180°, 270°
Paper width	57 mm
Paper weight	from 55 to 60 g/m ²
Paper thickness	61⊠m
Printing width	48 mm
Roll Dimension	max Ø 33mm +/- 1 mm
Emulation	CUSTOM / POS
Interfaces	USB + Bluetooth
Data Buffer	2 KB
Flash Memory	512 KB
Supported Bluetooth Profile	SPP (Serial Port Profile), OPP (Object Push Profile)
Drivers	Windows® (32/64 bit) – only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit); Android™; iOS
Software Tools	PrinterSet, CustomPowerTool, Custom Windows API
Power supply	Input: from 100 Vac to 240 Vac Output: 5 V± 10%
Medium consumption	500mA (12,5% printing rate)
Operating temperature	-20°C + 70°C
Safety	EN60950 2001
Marks	Bluetooth, CE, RoHS compliant
Dimensions	110 (L) x 45 (H) x 85 (W) mm
Weight	205 gr

MODELS



911CP010300A33









Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: 8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 13 March 2024







